



### Installation Method



Ashlar Herringbone

Interface European Manufacturing BV reserve the right to change or modify specifications.

**Product** Natural Woodgrains **Colour** A00207 Washed Wheat

### Product Specifications

|                      |   |
|----------------------|---|
| Product Number       | A002  |
| Product Construction | High Performance Luxury Vinyl Tile Contains 39% Pre-Consumer Recycled Content |
| Finish               | Ceramor™ - UV Stabilised Ceramic Bead Coating                                 |
| Wear Layer Thickness | (EN ISO 24340) 0.55 mm  |
| Total Thickness      | (EN ISO 24346) 4.5mm  |
| Total Weight         | (EN ISO 23997) 6880 g/m <sup>2</sup>  |
| Size – Packaging     | 25 x 100 cm – 2.5 m <sup>2</sup> Box  |
| Backing              | Sound Choice™ Acoustic Backing  |

### Performance Specifications

|   |  |               |
|---|--|---------------|
| Wear Classification                                       | EN ISO 10874 33 Heavy Commercial / 42 General Light Industrial |               |
| CE Declaration Of Performance                             | <a href="#">DOP PBRG-AHCK3R</a>                                |               |
| Castor Chair Rating                                       | (ISO 4918 / EN425) Pass  |               |
| Flammability  | (EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)                  |               |
| Light Fastness  | ≥7 (ISO 105-B02)   |               |
| Light Reflectance Value (LRV)                             | LRV – L value  | LRV – Y value |
|   | 59.2   | 27.3          |
| Dimensional Stability                                     | (ISO 23999) ≤ 0.25%  |               |
| Curling   | (ISO 23999) ≤ 2 mm   |               |
| Flexibility   | (EN ISO 24344) Method A - Pass.                                |               |
| Abrasion Resistance                                       | (EN 660-2) Group T   |               |
| Residual Indentation                                      | mm(EN ISO 24343-1) ≤ 0.2                                       |               |
| Determination of Anti-Slip                                | (DIN 51130) R9   |               |
| Chemical Resistance                                       | (EN ISO 26987) Very Good                                       |               |
| Impact Sound Insulation ΔL <sub>w</sub><br>EN ISO 10140-3 | 16 dB  |               |

### Environmental Specifications

|                                       |   |
|---------------------------------------|---|
| Total Recycled Content                | 39%   |
| Indoor Air Quality                    | French A+<br><a href="#">Indoor Air Comfort GOLD®</a>                           |
| Potential Green Building Contribution |   |
| Environmental Product Declaration     | <a href="#">MR-ULE-EPD-INF-20170001-EN</a>                                      |
| Full Life Cycle Carbon Footprint      | According to EPD or EPD calculation method                                      |
| Embodied Carbon (Cradle to Gate)      | 12.4 kg CO <sub>2</sub> eq./m <sup>2</sup>                                      |
| Full Life Cycle Carbon                | Certified Carbon Neutral Floors™  |
| End of Life Options                   |   |
| ReUse                                 | Can be cleaned and reused in a non-critical location to extend its useful life. |
| Fully Recyclable                      | Can be recycled into carpet tile backing.                                       |
| Material Composition                  | Free of Ortho Phthalates  |

### Technical Information

|              |   |
|--------------|---|
| Installation | <a href="#">See recommended LVT installation guidelines</a> |
| Maintenance  | <a href="#">See recommended LVT maintenance guidelines</a>  |
| Warranty     | 15 years  |

### Performance Qualifications

|  |  |        |    |  |       |    |  |                         |  |  |  |  |  |  |
|--|--|--------|----|--|-------|----|--|-------------------------|--|--|--|--|--|--|
|  |  |        |    |  |       |    |  |                         |  |  |  |  |  |  |
|  |  | Bfl-s1 | BS |  | 16 dB | ≥7 |  | 0.03 m <sup>2</sup> K/W |  |  |  |  |  |  |

### Certifications

**CE**

---

17

---

Interface European Manufacturing B.V.  
 Industrielaan 15  
 3925 BD  
 Scherpenzeel  
 The Netherlands

---

**DOP PBRG - AHCK3R**

---

EN 14041:2004  
 Notified Body - 0321

---

Resilient floor covering for internal use.

|                  |   |
|------------------|---|
| Classification   | Class 33/42 (EN ISO 10874)              |
| Reaction to fire | Class Bfl-s1 (see EN 14041, clause 4.1) |
| Slip resistance  | Class DS (See EN 14041, clause 4.5)     |
| Formaldehyde     | E1 (see EN 14041, clause 4.3)           |
| Anti-static      | < 2.0kV (See EN14041, clause 4.6.1)     |

---

[www.interface.com/lv-emea](http://www.interface.com/lv-emea)

